

technical data: blanking press

Model #		Two point					Four point		
		S2C-400	S2C-500	S2C-630	S2C-800	S2C-1600	S4C-500	S4C-630	S4C-800
Nominal capacity	kN	4000	5000	6300	8000	16000	5000	6300	8000
Nominal stroke	mm	5	13	6	10	15	6	13	6.5
Slide stroke	mm	300	500	300	300	200	300	350	250
Strokes of slide	spm	10~60	20~40	12~20	20	13	15~60	15~65	20~80
Shut height (SDAU)	mm	450	1000	500	700	700	1100	1250	950
Slide adjustment	mm	230	250	250	400	300	350	400	300
Bolster area (FB x LR)	mm	1800 x 2200	1800 x 3500	1400 x 2500	1550 x 2800	2000 x 4000	2500 x 5000	2750 x 5000	2500 x 4600
Slide bottom area (FB x LR)	mm	1800 x 2200	1800 x 3500	1400 x 2500	1550 x 2800	1800 x 4000	2500 x 5000	2750 x 5000	2500 x 4600
Height above floor	mm	7000	8500	5800	7600	8100	9000	9200	8500
Overall dimension (FB x LR)	mm	5675 x 6400	5300 x 6700	3800 x 4700	3820 x 5800	6000 x 7500	6500 x 8500	7000 x 7100	7500 x 7000