

technical data: straight-sided four-point single action eccentric drive mechanical press

Model #		S4-500	S4-630	S4-800	S4-1000	S4-1200	S4-1300	S4-1400	S4-1600	S4-2000	
Nominal capacity	kn	5000	6300	8000	10000	12000	13000	14000	16000	20000	
Nominal stroke	mm	13	13	13	13	13	13	13	13	13	
Slide stroke	mm	1000	1000	1000	1100	1100	1000	1000	800	800	
Strokes of slide	spm	8~18	10~18	9~18	10~20	6~20	9~18	8~20	8~16	10~25	
Shut height (SDAU)	mm	1300	1300	1400	1500	1400	1400	1400	1500	1200	
Slide adjustment	mm	500	700	600	700	700	600	600	650	400	
Bolster area (FB x LR)	mm	2300 x 4200	2400 x 4200	2600 x 5000	2500 x 5000	2500 x 5000	2600 x 5000	2500 x 5000	2500 x 6000	2300 x 6250	
Slide bottom area (FB x LR)	mm	2300 x 4200	2400 x 4200	2600 x 5000	2500 x 5000	2500 x 5000	2600 x 5000	2500 x 5000	2500 x 6000	2300 x 6250	
Cushion	Capacity	kN	--	1500	2000	3000	2500	2500	--	3000	1250
	Stroke	mm	--	0~250	0~250	0~350	0~350	0~250	--	50~350	0~250
Height above floor	mm	11000	10000	11500	10000	11000	11500	10500	10200	10500	
Overall dimension (FB x LR)	mm	400 x 6200	7000 x 7500	4100 x 7000	4250 x 7200	4250 x 7200	4200 x 7100	4200 x 6400	7000 x 8600	8000 x 9000	