

technical data: straight-sided, one-point single action mechanical press														
Model #		S1-250	S1-315	S1-400	S1-500	S1-630	S1-800	S1-1000	S1-1250	S1-1600	S1-2000	S1-2400	S1-2500	
Nominal capacity	kN	2500	3150	4000	5000	6300	8000	10000	12500	16000	20000	24000	25000	
Nominal stroke	mm	10.4	10.5	13	13	13	13	20	13	13	13	20	25	
Slide stroke	mm	315	315	400	400	500	500	500	500	500	500	600	500	
Strokes of slide	spm	20	20	20	16	10~20	10~20	8~14	8~14	8~14	7~10	12	10~16	
Shut height (SDAU)	mm	400	490	550	600	700	700	1100	950	1400	1400	1000	1000	
Slide adjustment	mm	200	200	250	250	250	315	750	400	500	500	500	250	
Bolster area (FB x LR)	mm	950 x 1000	1100 x 1100	1200 x 1240	1400 x 1700	1500 x 1700	1600 x 1900	1600 x 1800	1800 x 1800	1800 x 1920	2000 x 1800	1600 x 1900	1750x2000	
Slide bottom area (FB x LR)	mm	850 x 980	960 x 1070	1000 x 1230	1300 x 1680	1400 x 1680	1500 x 1860	1600 x 1800	1800 x 1800	1800 x 1920	2000 x 1800	1600 x 1900	1750x2000	
Cushion	Capacity	kN	--	76	76	76	150	180	500	500	800	500	1200	2000
	Stroke	mm	--	160	200	200	250	250	250	250	250	250	200	250
Height above floor	mm	6700	6620	7473	7150	8500	9000	11000	9500	10200	10000	10500	10500	
Overall dimension (FB x LR)	mm	2645 x 1890	2520 x 2416	2650 x 3260	4200 x 3980	4900 x 4200	5000 x 4500	6600 x 5700	5900 x 6600	6100 x 6600	4600 x 6600	8700 x 7750	5500x7200	