

technical data: transfer press, link & eccentric driven													
Model #		TE4-1000	TE4-1500	TE4-2000	TE4-2500	TE4-3000	TE4-3500	TLS4-1000	TLS4-1500	TLS4-2000	TLS4-2500	TLS4-3000	TLS4-3500
Drive type		Eccentric drive						Link drive					
Nominal capacity	kN	10000	15000	20000	25000	30000	35000	10000	15000	20000	25000	30000	35000
Nominal stroke	mm	13	13	13	13	13	13	13	13	13	13	13	13
Slide stroke	mm	500	500	600	600	700	700	600	700	700	800	800	800
Strokes of slide	spm	15~30	15~30	10~25	10~25	10~25	10~25	15~30	15~30	10~25	10~25	10~25	10~25
Shut height (SDAU)	mm	1100	1100	1100	1100	1200	1200	1100	1100	1100	1100	1200	1200
Slide adjustment	mm	300	300	300	300	300	300	300	300	300	300	300	300
Bolster area (FB x LR)	mm	2200 x 5000	2200 x 5000	2400 x 6100	2400 x 6100	2400 x 6500	2400 x 6500	2200 x 5000	2200 x 5000	2400 x 6100	2400 x 6100	2400 x 6500	2400 x 6500
Slide bottom area (FB x LR)	mm	2200 x 5000	2200 x 5000	2400 x 6100	2400 x 6100	2400 x 6500	2400 x 6500	2200 x 5000	2200 x 5000	2400 x 6100	2400 x 6100	2400 x 6500	2400 x 6500
Cushion (first station)	Capacity	kN		800	800	1200	1200			1200	1200	1500	1500
	Stroke	mm		200	200	250	250			200	200	250	250