

technical data: straight-sided two-point single action eccentric drive mechanical press												
Model #		S2-250	S2-300	S2-400	S2-500	S2-630	S2-800	S2-1000	S2-1250	S2-1600	S2-4000	
Nominal capacity	kN	2500	3000	4000	5000	6300	8000	10000	12500	16000	40000	
Nominal stroke	mm	13	13	13	13	13	13	13	13	15	25	
Slide stroke	mm	400	700	500	700	600	600	600	600	650	650	
Strokes of slide	spm	9~20	10~20	10~20	10~18	10~20	10~20	10~20	8~16	9~16	6~10	
Shut height (SDAU)	mm	750	900	850	1000	1100	1250	1200	1400	1200	1200	
Slide adjustment	mm	300	400	400	400	600	600	600	700	700	500	
Bolster area (FB x LR)	mm	1250 x 2560	1500 x 2800	1660 x 2800	1800 x 4000	1800 x 4000	1800 x 4000	1800 x 4500	1800 x 4000	1800 x 4000	1800 x 10000	
Slide bottom area (FB x LR)	mm	1250 x 2770	1500 x 2800	1660 x 2800	1800 x 4000	1800 x 4000	1800 x 4000	1800 x 4500	1800 x 4000	1800 x 4000	1800 x 10000	
Cushion	Capacity	kN	400	800	1000	1500	1500	2000	2000	2000	2000	8 x 1000
	Stroke	mm	0~200	0~200	0~240	0~250	0~250	0~300	0~250	0~250	0~250	0~250
Height above floor	mm	6752	8000	7500	9000	9000	9000	9300	10000	9500	11800	
Overall dimension (FB x LR)	mm	2800 x 5000	5700 x 4620	3500 x 4200	5000 x 7000	6500 x 7000	3700 x 7000	6000 x 9000	3500 x 6500	3800 x 5500	7300 x 15300	