

technical data: straight-sided four-point single action link drive mechanical press																
Model #		LS4-630	LS4-800	LS4-1000	LS4-1200	LS4-1300	LS4-1400	LS4-1500	LS4-1600	LS4-1800	LS4-2000	LS4-2100	LS4-2250	LS4-2400	LS4-2500	
Nominal capacity	kN	6300	8000	10000	12000	13000	14000	15000	16000	18000	20000	21000	22500	24000	25000	
Nominal stroke	mm	12	13	13	13	13	13	13	13	13	13	25	13	13	13	
Slide stroke	mm	750	1000	1000	1000	1000	1000	1000	1200	1100	1100	1400	1000	1200	1350	
Strokes of slide	spm	8~18	10~18	10~18	8~18	10~20	10~20	7~18	8~20	10~18	10~18	8~20	6~16	10~18	8~16	
Shut height (SDAU)	mm	900	1350	1300	1425	1300	1500	1450	1400	1400	1400	1525	1500	1300	1530	
Slide adjustment	mm	400	600	600	500	600	700	660	600	700	550	375	500	500	530	
Bolster area (FB x LR)		mm	1800 x 3200	2000 x 4000	2000 x 4000	2400 x 4500	2200 x 4000	2300 x 3500	2500 x 4600	2600 x 4600	2500 x 4600	2500 x 5000	2400 x 4500	2400 x 4500	2500 x 5000	2500x 5000
Slide bottom area (FB x LR)		mm	1800 x 3200	2000 x 4000	2000 x 4000	2400 x 4500	2200 x 4000	2300 x 3500	2500 x 4600	2600 x 4600	2500 x 4600	2500 x 5000	2400 x 4500	2400 x 4500	2500 x 5000	2500 x 5000
Cushion	Cap.	kN	1200	1500	2500	2500	3000	3000	3500	3200	4000	3000	NC6000	NC4500	NC4000	NC4500
	Stroke	mm	0~250	0~300	0~300	0~250	0~300	0~300	0~300	0~300	0~350	0~300	0~350	0~300	0~350	0~350
Height above floor		mm	9000	10000	10700	11000	11000	11500	12000	11500	12000	11500	13000	12000	12000	12000
Overall dimension (FB x LR)		mm	6300 x 6400	6800 x 7300	4000 x 6500	7500 x 8500	4200 x 7000	4500 x 7000	7000 x 8198	7900 x 8300	5000 x 8000	9250 x 7700	4750 x 8000	4200 x 8500	8000 x 7700	4600 x 9200